

SHIPPED: JANUARY 2015



S.P.S.
Seguridad Protección & Soldadura S.A.S.
Nuestro compromiso



ULTRA-HIGH PRESSURE PUMP

An EJM triple plunger ultra-high pressure shall be provided. The UHP pump shall have the following features:

- 6 GPM @ 1800 PSI
- Die cast aluminum crankcase
- Stainless steel valves and seats
- Chrome-Moly crankshaft
- Oversized bearings
- Brass in-let manifold
- Stainless steel discharge manifold
- Specially formulated high pressure seals

70 WATER - 5 FOAM

PUMP ENGINE

The EJM Ultra-High Pressure pump shall be powered by A Honda GX630 gasoline engine.

- | | |
|---------------------|---|
| Engine Type: | Air-cooled 4-stroke OHV |
| Bore & Stroke: | 78mm x 72mm |
| Displacement: | 688 cc3 |
| Net Torque: | 35.6 lb-ft. @ 2500 RPM |
| PTO Shaft Rotation: | Counterclockwise |
| Compression Ratio: | 9.3:1 |
| Lamp/Charge Coil: | 2.7A, 17A, 26A |
| Carburetor: | Horizontal type, 2-barrel
Butterfly valve, internal vent |
| Ignition System: | Digital CDI w/variable ignition timing |
| Starting System: | Electric |
| Lubrication System: | Forced lubrication |
| Governor System: | Mechanical |
| Air Cleaner: | Dual Element |
| Oil Capacity: | 2.1 US Quarts |
| Fuel: | Unleaded Gasoline 86 Octane min. |
| Dry Weight: | 96.8 lbs. |
| Dimensions: | Length - 15.9"
Width - 16.1"
Height - 17.2" |
| Fuel Consumption: | 1.59 Gal/Hr. @ full load |



1201 MAPLE CREEK LANE

FAX
920-779-9914

WEB
ejmetals.com



NEW LONDON, WI 54961 - 920-779-9913

S.P.S.
 Seguridad Protección & Soldadura S.A.S.
 Nuestro compromiso

COLOMBIAN EXPORT



**** 70 WATER ****
**** 5 FOAM ****

MANUAL REWIND UHP HOSE REEL

EJM Tri-Plex Water / Foam Nozzle
150 Feet US Mil-Spec UHP hose
Manual rewind handle
Manual friction brake

