

**DELIVERED:
DECEMBER, 2014**



ENGINE DRIVEN PUMP MODULE

A triplex plunger high pressure ceramic lined pump will be provided. The pump specifications are listed as follows.

- Model 5150-EJM Triple Plunger High Pressure Pump
- 6 GPM @ 1800 PSI
- Chrome-Molly Crankshaft
- Shaft Protector
- Oversized Bearings
- Stainless Steel Valves and Valve Seats
- Brass Manifold
- Die Cast Aluminum Crank Case
- Inlet Inductor
- Inlet Strainer
- Pop-off Pressure Relief Valve - (pre-set)
- Thermal Relief Valve - (prevents overheating of by-pass loop)

**6 GPM @ 1800 PSI UHP
Patient
Transport Unit**



**50 Water
5 Foam**



PUMP ENGINE

Honda, Model GX390 with the following specifications.

- 13-Horse Power @ 3600 RPM
- Air-Cooled, 4-Stroke, OHV, Single Cylinder
- Electric Start with manual recoil back-up
- Dual Element Air Cleaner
- 3 Gallon Fuel Tank
- 1.16 Quart Oil Capacity
- Commercial Grade
- Horizontal Shaft
- Digital CDI Ignition
- Oil Alert
- EPA/CARB Compliant
- 3-Year Commercial Warranty
- 12-volt battery



50 Water 5 Foam

ATTENDANT SEAT



PATIENT TRANSPORT, SEPARATE COMPONENT

A slide-in patient transport module will be provided that will fit inside the Polaris Ranger rear dump box. Included in the design of the module will be provisions for securing a stokes basket (not included) for patient transport. A seat will be installed near the head of the patient to allow a first responder to attend to the victim while the person is being transported.



OXYGEN BOTTLE STORAGE CABINET

Provided behind the attendant seat will be a custom built cabinet for the storage of two (2) spare oxygen bottles. The cabinet will be constructed from .125" bright aluminum diamond plate material. There will be storage slots for two (2) oxygen bottles that measure approximately 14.00" long with a 5.00" diameter. The storage slots open to the passenger side and will be angled downward to hold them in place. The remaining area of the cabinet will provide a storage space accessible from the driver's side of the unit. The driver's side storage compartment will be provided with a .125" bright aluminum diamond plate door. A full length .25" stainless steel hinge will be provided along with a push to release trigger latch to keep the door closed.



FAX
920-779-9914

WEB
ejmetals.com

